

MONOCOAT Oil Plus or 2C Oil Plus Part A

HARDWAX OIL

PROTECTS AND COLORS YOUR WOOD WITH ONE COAT

SPECIFIC FEATURES:

Rubio Monocoat Oil Plus colors and protects your wood in one layer. Unlike traditional hardwax oils, Rubio Monocoat Oil Plus will connect with wood fibers by means of a molecular reaction, a result of which a durable protection is obtained. This molecular connection enables Rubio Monocoat Oil Plus to embed in the surface's upper microns immediately. The wood fibers can only combine with a certain amount of oil. Oil, which has not reacted, does not adhere and needs to be removed.

RENOVATION:

Where scratches or gouges are present, or where heavy wear is showing (either in patches or large areas of the floor) a renovation treatment with Rubio Monocoat Oil Plus is recommended. Local repair is easy: only the wood fibers which have become oil free from damage will combine with new oil. Recoating with a completely new color over the entire surface of a previously treated floor is possible. Please consult our instructions sheet on renovation

DRYING TIME:

Provided that the room is well ventilated, the surface is useable after 36 hours. Areas with **very** heavy traffic can be protected with cardboard during the first week, but only during the traffic period.

MAINTENANCE:

After treatment with Rubio Monocoat Oil Plus, the floor requires 3 weeks to harden completely. During the first week, it is advisable to only clean with a vacuum cleaner or a dust mop. Do NOT use damp cloths! After the second week, a damp cloth soaked in clean water and wrung out thoroughly, can be used with due care. After 3 weeks, the floor can be maintained using maintenance products from the Rubio Monocoat range.

www.monocoat.us/Maintenance/

SAFETY:

Rubio Monocoat Oil Plus is 100% environmentally friendly.

TRANSPORT:

There are no specific measures to be taken for transport by road, sea or air.

INSTRUCTIONS:

Consult our website for full instructions.

www.monocoat.us/Application-Procedures/

- 100 % VOC-FREE!

- Respects the natural 'look and feel' of the wood
- Low consumption - 1 liter for 300 to 500 sq. ft.
- No starting marks or overlaps
- 34 standard colors
- Easy to maintain
- Doesn't contain water
- For use on all kinds of wood (solid wood, veneer wood, MDF, etc...)
- Durable protection, highly resistant to wear
- Resistant to heat up to 212 °F
- Water-resistant: (suited for kitchens and baths)

TECHNICAL SPECIFICATIONS:

Basis: mixture of natural oils and hardwax.

Color: 34 standard colors.

Consistency: liquid

Flash point: cc (astm d93): > 215°F (PenskyMartens)

Fixed dust percentage: > 90%

Density: Pure: 0.93 g/cm³ - colors: from 1 to 1.4 g/cm³

VOC: 0 g/l (2004/42/CE, 1999/13/CE)

Resistance to water (NEN-EN 13442): no visual or tangible changes

Resistance to wear: (NEN 2072 – Taber Abraser en CS 17 sanding wheels): strong absorption basantol liquid, only after 800 to 1000 rotations.

Resistance to heat until 212 °F

STORAGE:

The product can be stored up to 24 months. Store in dry conditions and in the original packaging.

PACKAGING:

20 ml - 100 ml – 275 ml. - 1 liter can

PRECAUTION:

The product may NOT be diluted!

Cloths, saturated with oil, may spontaneously combust. After usage, they need to be soaked in water before disposal.

CONSUMPTION:

Pure Oil - 1 liter / +/- 500 sq. ft.

Color Oil - 1 liter / +/- 350 sq. ft.